

Combi oven

maxx 20.20 ES

Convotherm maxx
 easyTouch

20.20
 20 Shelves GN 2/1

Electric
 Injection/Spritzer
 Right-hinged door

Key features



- Cooking methods: Steam, Combi-steam, Convection
 Extra functions:
- Crisp&Tasty – Moisture removal in 3 levels
 - HumidityPro – Moisture input in 3 levels
 - BakePro – Traditional baking function in 3 levels
 - Fan with 3 speed settings
- easyTouch 7" TFT HiRes glass touch display (capacitive)
 Fully automatic cleaning system with 5 programs: Quick Rinse, CareStep, Light, Heavy and Express mode
 Wi-Fi and Ethernet interface (LAN)
 USB port integrated in the operating panel
 Steam generation by injecting water into the cooking chamber
 LED lighting in the cooking chamber
 Appliance door with double glazing, right-hinged

Standard features

- Cooking methods:
- Steam (30-130°C) with guaranteed steam saturation
 - Combi-steam (30-250°C) with automatic moisture control
 - Convection (30-250°C) with optimized heat transfer
- Operation of easyTouch user interface:
- 7" TFT HiRes glass touch display (capacitive)
 - Smooth-action, quick-reacting scrolling function
- Climate Management:
- SelfClimateControl
 - HumidityPro
 - Crisp&Tasty
- Quality Management:
- Airflow Management
 - BakePro
 - Multi-point core temperature probe
 - Preheat and cool down function
- Cleaning Management:
- Fully automatic cleaning system with 5 programs: Quick Rinse, CareStep, Light, Heavy and Express mode
 - FilterCare interface

Standard features

- Production Management
- Automatic cooking with Press&Go with up to 399 profiles
 - Integrated cookbook with 7 different categories
 - Cooking different products with Press&Go
 - Favourites management
 - HACCP data storage
 - USB port
 - LT cooking (low-temperature cooking)
 - AutoStart
 - Manager and crew mode with password protection
 - Message Step – Displays preparation instructions
 - Add steam - introduction of moisture in Convection mode as required
- HygieniCare:
- Hygienic Steam function
 - Hygienic handles (door and hand-shower handles)

IPX5 CE

Convotherm maxx
easyTouch

- 20.20
- 20 Shelves GN 2/1
- Electric
- Injection/Spritzer
- Right-hinged door



Key features

- Cooking methods: Steam, Combi-steam, Convection
- Extra functions:
 - Crisp&Tasty – Moisture removal in 3 levels
 - HumidityPro – Moisture input in 3 levels
 - BakePro – Traditional baking function in 3 levels
 - Fan with 3 speed settings
- easyTouch 7" TFT HiRes glass touch display (capacitive)
- Fully automatic cleaning system with 5 programs: Quick Rinse, CareStep, Light, Heavy and Express mode
- Wi-Fi and Ethernet interface (LAN)
- USB port integrated in the operating panel
- Steam generation by injecting water into the cooking chamber
- LED lighting in the cooking chamber
- Appliance door with double glazing, right-hinged

Standard features, continued

- Design:
 - Appliance door with double glazing and sure-shut function
 - Right-hinged door and LED cooking chamber lighting
 - Steam generation by injecting water into the cooking chamber
 - Adjustable appliance feet to compensate for level differences
 - Multi-point core temperature probe
 - Integrated recoil hand shower
 - Shape-optimised wheel-in rails
 - Integral preheat bridge


Options

- Available in various voltages


Accessories

- Production Management: KitchenConnect® (Wi-Fi/LAN), network solution from Welbilt for updating and monitoring appliances from anywhere
- ConvoVent 4 condensation hood with grease filter
- ConvoVent 4+ condensation hood with grease and odour filter
- Care products for the fully automatic cleaning system
- Various baking trays, shelf grills, gastronorm containers
- Heat shield

Front view




Connection points



- A Water connection (for water injection)
- B Water connection (for cleaning, recoil hand shower)
- C Drain connection, DN 50
- D Electrical connection
- E Protective equipotential bonding
- F Rinse-aid connection
- G Cleaning-agent connection
- H Air vent connection Ø50mm
- I Ventilation port Ø50mm
- M Safety overflow 80 x 25 mm
- N RJ45 Ethernet port

View from above with wall clearances



Dimensions and weights

Dimensions including packaging

Width x Height x Depth 1415 x 2150 x 1150 mm

Weight

Empty weight without packaging 340 kg

Weight of packaging 34.5 kg

Safety clearances*

Rear 50 mm

Right* 50 mm

Left* 50 mm

Top** 500 mm

* Required for the appliance to function.

** Depends on type of air ventilation system and nature of ceiling.

Installation instructions

Clearance from heat sources min. 500 mm

Recommended clearance for service, left appliance side min. 500 mm

Adjustable appliance feet* max. 30 mm

* Fully screwed in illustrations

Food capacity

Max. number of food containers	
GN 1/1*	40
GN 2/1*	20
Maximum loading weight	
GN 1/1 / GN 2/1	
Per combi oven	180 kg
Per shelf level	15 kg

* Matching loading trolley included as standard.

Electrical supply

3N~ 400V 50/60Hz*	
Rated power consumption	67.3 kW
Rated current	97.3 A
Fuse rating	100 A
RCD (GFCI), single-phase frequency converter	Type A or type B
Recommended conductor cross-section	5G35
3~ 220V 60Hz (3/PE)	
Rated power consumption	60.8 kW
Rated current	159 A
Fuse rating	160 A
RCD (GFCI), single-phase frequency converter	Type A or type B
Recommended conductor cross-section	4G70
3N~ 380V 60Hz	
Rated power consumption	60.7 kW
Rated current	92.2 A
Fuse rating	100 A
RCD (GFCI), single-phase frequency converter	Type A or type B
Recommended conductor cross-section	5G35
3~ 200V 50/60Hz*	
Rated power consumption	66.4 kW
Rated current	192 A
Fuse rating	200 A
RCD (GFCI), single-phase frequency converter	Type A or type B
Recommended conductor cross-section	4G95

* Connection to energy optimization system included as standard.

Water connection

Water supply

Water supply connection	2 x G 3/4" fixed connection, optionally including connecting pipe (min. DN13 / 1/2")
Water supply safety device	For UK: With double non-return valve DCV (type CA) and dirt filter*
Flow pressure	150 - 600 kPa (1.5 - 6 bar)

Appliance drain

Drain version	Fixed connection (recommended) or open tank or channel/gully. Due to possible vapours, open drains or ducts must be at least 60 cm beyond the base of the appliance.
Type	DN 50 (min. internal Ø: 46 mm)
Slope for drain pipe	min. 3.5% (2°)

* Backflow prevention up to at least liquid category 3 in accordance with EN 1717

Water quality

Water connection A* for water injection

General requirements	Drinking water, typically soft water (install water treatment system if necessary)
General hardness**	4 - 7 °dh / 70 - 125 ppm / 7 - 13 °TH / 5 - 9 °e

Water connection B* for cleaning, recoil hand shower

General requirements	Drinking water, typically hard water
General hardness**	4 - 20 °dh / 70 - 360 ppm / 7 - 35 °TH / 5 - 25 °e

Water-supply connections A, B*

pH value	6.5 - 8.5
Cl ⁻ (chloride)	max. 60 mg/l
Cl ₂ (free chlorine)	max. 0.2 mg/l
SO ₄ ²⁻ (sulphate)	max. 150 mg/l
Fe (iron)	max. 0.1 mg/l
SiO ₂ (silicate)	max. 13 mg/l
NH ₂ Cl (monochloramine)	max. 0.2 mg/l
Temperature	max. 40 °C
Electrical conductivity	min. 20 µS/cm

* See diagram of connection points, page 3.

** Despite compliance with the total hardness limits, non-hardness deposits may occur in certain cases. Measures must be coordinated with the technical service.

Water consumption

Water connection A*

Ø Consumption for cooking**	11.8 l/h
Max. water flow rate	0.8 l/min

Water-supply connections A, B

Ø Consumption for cooking**	17.7 l/h
Max. water flow rate	15 l/min

* Values for selecting the capacity of the water treatment system.

** Including water used for cooling the wastewater.

PLEASE NOTE: See diagram of connection points, page 3.

Emissions

Dissipated heat*

Latent heat	11000 kJ/h / 3.06 kW
Sensible heat	14100 kJ/h / 3.92 kW
Ø Waste water temperature	max. 80 °C
Noise during operation	max. 70 dBA

* The dissipated heat values were measured as per DIN 18873-1 "Methods for measuring the energy use of equipment for commercial kitchens — Part 1".

The type and frequency of appliance usage are decisive for the specification of an air conditioning and ventilation system. These values can be higher than the values indicated for dissipated heat. Guide values can be found in the technical literature, e.g. in VDI 2052.

Please consult your specialized design engineer for planning an air conditioning and ventilation system.

Appliance type

Approval designation	C4 eT 20.20 ES
----------------------	----------------

ACCESSORIES

(Further details on accessories can be found in the Product Info Portal at <https://productinfo.convotherm.com>)

ConvoVent 4 condensation hood

Electrical supply	
Rated voltage	1N~ 200-240V 50/60Hz
Rated power consumption	130-260 W
Rated current	1.0-1.9 A
Fuse rating	2.5 A
Dimensions excluding packaging	
Width x Height x Depth	1137 x 240 x 1285 mm
Weight excluding packaging	97 kg
Safety clearance above**	500 mm

** Depends on type of air ventilation system and nature of ceiling.

ConvoVent 4+ condensation hood

Electrical supply	
Rated voltage	1N~ 200-240V 50/60Hz
Rated power consumption	130-260 W
Rated current	1.0-1.9 A
Fuse rating	2.5 A
Dimensions excluding packaging	
Width x Height x Depth	1137 x 373 x 1285 mm
Weight excluding packaging	120 kg
Safety clearance above**	500 mm

** Depends on type of air ventilation system and nature of ceiling.

Please observe the following points:

- This document is to be used solely for planning purposes.
- Further technical data as well as installation and set-up instructions can be found in the Product Info Portal at <https://productinfo.convotherm.com>.

9772558_00_ENG_GBR 11/25, © 2025 Welbilt. Continuous improvements to the product may mean changes to the specification are made without explicit mention.